

TECHNICAL DATA

Code	Wattage	Luminous Flux				Size (Ø X H)mm
		2700K	3000K	4000K	5000K	
BLU-IS-M	6W	500	525	550	600	55 X 49
BLU-IS-M	8W	800	825	850	900	55 X 49
BLU-IS-2M	12W	1100	1125	1150	1200	55 X 72
BLU-IS-2M	13W	1300	1325	1350	1400	55 X 72
BLU-IS-3M	24W	2200	2225	2250	2300	70 X 90
BLU-IS-4M	28W	2600	2625	2650	2700	87 X 107
BLU-IS-4M	32W	3000	3025	3050	3100	87 X 107
BLU-IS-5M	35W	3300	3325	3350	3400	102 X 116
BLU-IS-5M	42W	3900	3925	3950	4000	102 X 116

Luminous Efficacy

>90lm/W

SDCM

<3

CRI

>83/93

Beam Angle

10°/15°/24°/38°/55°

Working Voltage

36 VDC

LED Driver

Remote

Control

Switched / 1-10V / DALI

Body Material

Die-cast Aluminium

Optics

PMMA

IP Rating

IP40

Working Temperature

-20°C to 40°C


Rated Life

50,000Hrs (L70)

ORDER INFORMATION

Product Code	X	YY	ZZ
BLU-IS-M-6W	8 - CRI 83+	27 -2700K	10 - 10 Deg
BLU-IS-M-8W	9 - CRI 93+	30 -3000K	15 - 15 Deg
BLU-IS-2M-12W		40 -4000K	24 - 24 Deg
BLU-IS-2M-13W		50 -5000K	38 - 38 Deg
BLU-IS-3M-24W		WD - Warm Dlm	55 - 55 Deg
BLU-IS-4M-28W			
BLU-IS-4M-32W			
BLU-IS-5M-35W			
BLU-IS-5M-42W			

Example: BLU-IS-M-6W-827-15



Specification subject to change without notice